

Zenith

● General Overview

General street lighting applications with 50-70% energy saving. It replaces HPSV lamps.

● Features

- ↳ Special Aluminum Die cast fixture with toughened glass
- ↳ Heat management compliance
- ↳ Lumen Efficacy - 100 Lumen/Watt
- ↳ Inbuilt SMPS power supply
- ↳ Easily adjustable for different pole diameters
- ↳ Separate electronic driver cabin
- ↳ Fully compliant to IS:10322 standards
- ↳ Weight - 12.200 kg

● Installation

- ↳ Easy to install with the help of C clamp
- ↳ Size - 735x320x100 mm



● Tested by ERDA, Vadodra

Technical Data

Product Code	Fixture Color	Operating Voltage	Power Consumption (W)	LUX under the pole @6m @9m @12m	LED Type	IP Rating	LED Color
56 89 06.48	White	90-270 V AC	60	58 18 11	Power LED	66	CW/WW
56 89 06.72	White	90-270 V AC	90	86 20 17	Power LED	66	CW/WW
56 89 06.96	White	90-270 V AC	120	115 34 27	Power LED	66	CW/WW
56 89 06.96.1	White	90-270 V AC	150	128 42 31	Power LED	66	CW/WW

* Black and Brown fixture colors also available.